

Formatting Syntax

[DokuWiki](#) supports some simple markup language, which tries to make the datafiles to be as readable as possible. This page contains all possible syntax you may use when editing the pages.

Simply have a look at the source of this page by pressing "Edit this page". If you want to try something, just use the [playground](#) page. The simpler markup is easily accessible via [quickbuttons](#), too.

Basic Text Formatting

DokuWiki supports **bold**, *italic*, underlined and monospaced texts. Of course you can **combine** all these.

```
DokuWiki supports bold, //italic//, __underlined__ and 'monospaced'
texts.
Of course you can __//'combine'//__ all these
```

Note that the formatting markers have to directly enclose the text, so **bold** with spaces inside the markers will not be formatted.

You can use _{subscript} and ^{superscript}, too.

```
You can use <sub>subscript</sub> and <sup>superscript</sup>, too
```

You can mark something as ~~deleted~~ as well.

```
You can mark something as <del>deleted</del> as well
```

Paragraphs are created from blank lines. If you want to **force a newline** without a paragraph, you can use two backslashes followed by a whitespace or the end of line.

This is some text with some linebreaks
Note that the two backslashes are only recognized at the end of a line
or followed by
a whitespace \\this happens without it

```
This is some text with some linebreaks\\ Note that the
two backslashes are only recognized at the end of a line\\
.or followed by\\ a whitespace \\this happens without it
```

You should use forced newlines only if really needed.

Links

DokuWiki supports multiple ways of creating links.

External

External links are recognized automatically: <http://www.google.com> or simply www.google.com - You can set the link text as well: [This Link points to google](#). Email addresses like this one: [.andi@splitbrain.org](mailto:andi@splitbrain.org) are recognized, too

```
DokuWiki supports multiple ways of creating links. External links are
recognized
automagically: http://www.google.com or simply www.google.com - You can set
link text as well: [[http://www.google.com|This Link points to google]].
Email
.addresses like this one: <andi@splitbrain.org> are recognized, too
```

Internal

Internal links are created by using square brackets. You can either just give a [pagename](#) or use an additional [link text](#)

```
Internal links are created by using square brackets. You can either just
give
.[[a [[pagename]] or use an additional [[pagename|link text
```

.[Wiki pagenames](#) are converted to lowercase automatically, special characters are not allowed 🚫

.You can use [namespaces](#) by using a colon in the pagename

```
.You can use [[some:namespaces]] by using a colon in the pagename
```

.For details about namespaces see 📖 [namespaces](#)

Linking to a specific section is possible, too. Just add the section name behind a hash character as known from HTML. This links to [this Section](#)

```
.[[This links to [[syntax#internal|this Section
```

:Notes

- .Links to [existing pages](#) are shown in a different style from [nonexisting](#) ones •
- DokuWiki does not use 🐪 [CamelCase](#) to automatically create links by default, but this behavior •
- .can be enabled in the 📖 [config](#) file. Hint: If DokuWiki is a link, then it's enabled
- When a section's heading is changed, its bookmark changes, too. So don't rely on section •
- .linking too much

Interwiki

DokuWiki supports 🐪 [Interwiki](#) links. These are quick links to other Wikis. For example this is a link to [Wikipedia's page about Wikis](#): 🐪 [Wiki](#)

DokuWiki supports `[[doku>Interwiki]]` links. These are quick links to other Wikis.
 .`[[For example this is a link to Wikipedia's page about Wikis: [[wp>Wiki`

Windows Shares

Windows shares like [this](#) are recognized, too. Please note that these only make sense in a .homogeneous user group like a corporate [Intranet](#)

.Windows Shares like `[[\\server\share|this]]` are recognized, too

:Notes

For security reasons direct browsing of windows shares only works in Microsoft Internet Explorer •
 .("per default (and only in the "local zone
 For Mozilla and Firefox it can be enabled through different workaround mentioned in the [Mozilla Knowledge Base](#). However, there will still be a JavaScript warning about trying to open a
 Windows Share. To remove this warning (for all users), put the following line in
 :`(conf/lang/en/lang.php` (more details at [localization](#)

[conf/lang/en/lang.php](#)

```
php?>
/**
 * Customization of the english language file
 * Copy only the strings that needs to be modified
 */
;'' = ['$lang['js']]['nosmblinks
```

Image Links

You can also use an image to link to another internal or external page by combining the syntax for
 :links and [images](#) (see below) like this

`[[{{http://php.net|{{wiki:dokuwiki-128.png}}`



.Please note: The image formatting is the only formatting syntax accepted in link names

The whole [image](#) and [link](#) syntax is supported (including image resizing, internal and external images

.(and URLs and interwiki links

Footnotes

.You can add footnotes ¹⁾ by using double parentheses

.You can add footnotes ((This is a footnote)) by using double parentheses

Sectioning

You can use up to five different levels of headlines to structure your content. If you have more than three headlines, a table of contents is generated automatically - this can be disabled by including the .string `~~NOTOC~~` in the document

Headline Level 3

Headline Level 4

Headline Level 5

```
Headline Level 3 =====  
==== Headline Level 4 ===  
== == Headline Level 5
```

:By using four or more dashes, you can make a horizontal line

Media Files

You can include external and internal  [images, videos and audio files](#) with curly brackets. Optionally .you can specify the size of them



:Real size



:Resize to given width



:²Resize to given width and height



:Resized external image

```
Real size:                {{wiki:dokuwiki-128.png}}
Resize to given width:    {{wiki:dokuwiki-128.png?50}}
Resize to given width and height: {{wiki:dokuwiki-128.png?200x50}}
Resized external image:
{{{https://www.php.net/images/php.gif?200x50
```

.By using left or right whitespaces you can choose the alignment



```
wiki:dokuwiki-128.png}} }}
{{wiki:dokuwiki-128.png }}
{{ {{ wiki:dokuwiki-128.png
```

You can also set the alignment explicitly with a ?left, ?right or ?center parameter. This takes precedence over the whitespace alignment above and can be combined with a size



```
{{wiki:dokuwiki-128.png?100&right}}
```

.Of course, you can add a title (displayed as a tooltip by most browsers), too



```
{{wiki:dokuwiki-128.png |This is the caption }}
```

.For linking an image to another page see [Image Links](#) above

Supported Media Formats

.DokuWiki can embed the following media formats directly

gif, jpg, png	Image
webm, ogv, mp4	Video
ogg, mp3, wav	Audio
swf	Flash

If you specify a filename that is not a supported media format, then it will be displayed as a link
.instead

By adding ?linkonly you provide a link to the media without displaying it inline

```
{{wiki:dokuwiki-128.png?linkonly}}
```

[.dokuwiki-128.png](#) This is just a link to the image

Fallback Formats

Unfortunately not all browsers understand all video and audio formats. To mitigate the problem, you
.can upload your file in different formats for maximum browser compatibility

:For example consider this embedded mp4 video

```
{{video.mp4|A funny video}}
```

When you upload a video.webm and video.ogv next to the referenced video.mp4, DokuWiki will
.automatically add them as alternatives so that one of the three files is understood by your browser

Additionally DokuWiki supports a “poster” image which will be shown before the video has started.
That image needs to have the same filename as the video and be either a jpg or png file. In the

.example above a video .jpg file would work

Lists

Dokuwiki supports ordered and unordered lists. To create a list item, indent your text by two spaces .and use a * for unordered lists or a - for ordered ones

```
                This is a list •
                The second item •
            You may have different levels ◦
                Another item •

                The same list but ordered .1
                Another item .2
            Just use indentation for deeper levels .1
                That's it .3
```

```
                This is a list *
                * The second item
            * You may have different levels
                * Another item

                - The same list but ordered
                - Another item
            - Just use indentation for deeper levels
                - That's it
```

.Also take a look at the [FAQ on list items](#)

Text Conversions

.DokuWiki can convert certain pre-defined characters or strings into images or other text or HTML

The text to image conversion is mainly done for smileys. And the text to HTML conversion is used for .typography replacements, but can be configured to use other HTML as well

Text to Image Conversions

DokuWiki converts commonly used [emoticons](#) to their graphical equivalents. Those [Smileys](#) and :other images can be configured and extended. Here is an overview of Smileys included in DokuWiki

```
(-8  •
O-8  •
)-:  •
```

(-: 😊 •
 (= 😄 •
 /-: 😞 •
 \-: 😞 •
 ?-: 😟 •
 D-: 😬 •
 P-: 😛 •
 O-: 😮 •
 X-: 🗑️ •
 |-: 😐 •
 (-; 😊 •
 ^ _ ^ 😄 •
)m 🙌 •
 :?: ❓ •
 :!: ❗ •
 LOL 🤣 •
 FIXME 🔧 **Fix Me!** •
 DELETEME 🗑️ **Delete!** •

Text to HTML Conversions

Typography: [DokuWiki](#) can convert simple text characters to their typographically correct entities.
 .Here is an example of recognized characters

"...'He thought 'It's a man's world" ® ™ © 480x640 — - » « ⇔ ⇐ ⇒ ⇔ ⇐ →

640x480 (c) (tm) (r) --- -- >> << <=> => <= <-> -> <-
 "...'"He thought 'It's a man's world

.The same can be done to produce any kind of HTML, it just needs to be added to the [pattern file](#)

There are three exceptions which do not come from that pattern file: multiplication entity (640×480), `'single'` and `"double quotes"`. They can be turned off through a [🐼 config option](#)

Quoting

Some times you want to mark some text to show it's a reply or comment. You can use the following syntax

```
I think we should do it
> No we shouldn't
>> Well, I say we should
> Really?
>> Yes!
!>>> Then lets do it
```

I think we should do it

No we shouldn't

Well, I say we should

?Really

!Yes

!Then lets do it

Tables

.DokuWiki supports a simple syntax to create tables

Heading 3	Heading 2	Heading 1
Row 1 Col 3	Row 1 Col 2	Row 1 Col 1
(some colspan (note the double pipe		Row 2 Col 1
Row 3 Col 3	Row 3 Col 2	Row 3 Col 1

.Table rows have to start and end with a `|` for normal rows or a `^` for headers

```
Heading 1      ^ Heading 2      ^ Heading 3      ^ ^
| Row 1 Col 1   | Row 1 Col 2   | Row 1 Col 3   |
| Row 2 Col 1   | some colspan (note the double pipe) ||
|               | Row 3 Col 1   | Row 3 Col 2   | Row 3 Col 3
```

To connect cells horizontally, just make the next cell completely empty as shown above. Be sure to !have always the same amount of cell separators

.Vertical tableheaders are possible, too

Heading 2	Heading 1	
Row 1 Col 3	Row 1 Col 2	Heading 3
	no colspan this time	Heading 4
Row 2 Col 3	Row 2 Col 2	Heading 5

:As you can see, it's the cell separator before a cell which decides about the formatting

```

Heading 1      ^ Heading 2      ^ ^
^ Heading 3    | Row 1 Col 2      | Row 1 Col 3    |
^ Heading 4    | no colspan this time |              |
|              ^ Heading 5      | Row 2 Col 2      | Row 2 Col 3

```

You can have rowspans (vertically connected cells) by adding :: into the cells below the one to .which they should connect

Heading 3	Heading 2	Heading 1
Row 1 Col 3		Row 1 Col 1
Row 2 Col 3	this cell spans vertically	Row 2 Col 1
Row 2 Col 3		Row 3 Col 1

.Apart from the rowspan syntax those cells should not contain anything else

```

Heading 1      ^ Heading 2      ^ Heading 3      ^ ^
| Row 1 Col 1  | this cell spans vertically | Row 1 Col 3    |
| Row 2 Col 1  | :::                      | Row 2 Col 3    |
|              | Row 3 Col 1      | :::              | Row 2 Col 3

```

You can align the table contents, too. Just add at least two whitespaces at the opposite end of your text: Add two spaces on the left to align right, two spaces on the right to align left and two spaces at .least at both ends for centered text

Table with alignment		
left	center	right
center	right	left
xxxxxxxxxxxxx	xxxxxxxxxxxxx	xxxxxxxxxxxxx

:This is how it looks in the source

```

Table with alignment      ^^^
|      right|    center  |left      |
|left      |      right|    center  |
| | xxxxxxxxxxxxx | xxxxxxxxxxxxx | xxxxxxxxxxxxx

```

.Note: Vertical alignment is not supported

No Formatting

If you need to display text exactly like it is typed (without any formatting), enclose the area either with `<nowiki>` tags or even simpler, with double percent signs `%%`.

This is some text which contains addresses like this: `http://www.splitbrain.org` and `**formatting**`, but nothing is done with it. The same is true for `//__this__ text//` with a smiley

```
nowiki>>
    This is some text which contains addresses like this:
http://www.splitbrain.org and **formatting**, but nothing is done with it.
</nowiki>
.%( -; The same is true for %//__this__ text// with a smiley
```

Code Blocks

You can include code blocks into your documents by either indenting them by at least two spaces (like used for the previous examples) or by using the tags `<code>` or `<file>`.

```
.This is text is indented by two spaces
```

```
This is preformatted code all spaces are preserved: like <-this
```

```
This is pretty much the same, but you could use it to show that you quoted a
file
```

:Those blocks were created by this source

```
.This is text is indented by two spaces
```

```
code>>
This is preformatted code all spaces are preserved: like <-this
<</code>
```

```
file>>
This is pretty much the same, but you could use it to show that you quoted a
file.
<</file>
```

Syntax Highlighting

[DokuWiki](#) can highlight sourcecode, which makes it easier to read. It uses the [GeSHi](#) Generic Syntax Highlighter – so any language supported by GeSHi is supported. The syntax uses the same code and file blocks described in the previous section, but this time the name of the language syntax to be highlighted is included inside the tag, e.g. `<code java>` or `<file java>`.

```

    */
    The HelloWorldApp class implements an application that *
    * simply displays "Hello World!" to the standard output.
    */
    class HelloWorldApp {
        public static void main(String[] args) {
            System.out.println("Hello World!"); //Display the string
        }
    }

```

The following language strings are currently recognized: 4cs 6502acme 6502kickass 6502tasm 68000devpac abap actionscript3 actionscript ada aimms algol68 apache applescript apt_sources arm asm asp asymptote autoconf autohotkey autoit avisynth awk bascomavr bash basic4gl batch bf biblatex bibtex blitzbasic bnf boo caddcl cadlisp ceylon cfdg cfm chaiscript chapel cil c_loadrunner clojure c_mac cmake cobol coffeescript c cpp cpp-qt cpp-winapi csharp css cuesheet c_winapi dart dcl dcpu16 dcs delphi diff div dos dot d_ecmascript eiffel email epc e erlang euphoria ezt f1 falcon fo fortran freebasic freeswitch fsharp gambas gdb genero genie gettext glsl gml gnuplot go groovy gwbasic haskell haxe hiest hq9plus html html4strict html5 icon idl ini inno intercal io ispfpanel java5 java javascript jcl j jquery julia kixtart klonex klonexcpp kotlin latex lb ldif lisp llvm locobasic logtalk lolcode lotusformulas lotusscript lscript lsl2 lua m68k magiksf make mapbasic mathematica matlab mercury metapost mirc mk-61 mmix modula2 modula3 mpasm mxml mysql nagios netrexx newlisp nginx nimrod nsis oberon2 objc object ocaml-brief ocaml octave oobas oorexx oracle11 oracle8 oxygene oz parasail parigp pascal pcre perl6 perl per pf phix php-brief php pic16 pike pixelbender pli plsql postgresql postscript povray powerbuilder powershell proftpd progress prolog properties providex purebasic pycon pys60 python qbasic qml q racket rails rbs rebol reg rexx robots roff rpmspec rsplus ruby rust sas sass scala scheme scilab scl sdlbasic smalltalk smarty spark sparql sql sshconfig standardml stonscript swift systemverilog tclegg tcl teraterm texgraph text thinbasic tsq1 twig typscript unicon upc urbi uscript vala vbnet vb vbscript vedit verilog vhd1 vim visualfoxpro visualprolog whitespace whois winbatch wolfram xbasic xml xoyo xorg_conf xpp yaml z80 zxbasic

There are additional  [advanced options](#) available for syntax highlighting, such as highlighting lines or adding line numbers

Downloadable Code Blocks

When you use the `<code>` or `<file>` syntax as above, you might want to make the shown code :available for download as well. You can do this by specifying a file name after language code like this

```

file php myexample.php>>
<?php echo "hello world!"; ?>
<</file

```

[myexample.php](#)

```

<? ;"!php echo "hello world?>

```

If you don't want any highlighting but want a downloadable file, specify a dash (-) as the language
code: `<code - myfile.foo`

RSS/ATOM Feed Aggregation

[DokuWiki](#) can integrate data from external XML feeds. For parsing the XML feeds, [SimplePie](#) is used. All formats understood by SimplePie can be used in DokuWiki as well. You can influence the rendering by multiple additional space separated parameters

Description	Parameter
will be used as maximum number items to show, defaults to 8	any number
display the last items in the feed first	reverse
show item authors names	author
show item dates	date
show the item description. All HTML tags will be stripped	description
do not sort the items in the feed	nosort
.(refresh period, where d=days, h=hours, m=minutes. (e.g. 12h = 12 hours	[n]dhm

The refresh period defaults to 4 hours. Any value below 10 minutes will be treated as 10 minutes. [DokuWiki](#) will generally try to supply a cached version of a page, obviously this is inappropriate when the page contains dynamic external content. The parameter tells [DokuWiki](#) to re-render the page if it is more than *refresh period* since the page was last rendered

By default the feed will be sorted by date, newest items first. You can sort it by oldest first using the .reverse parameter, or display the feed as is with nosort

:Example

```
{{ rss>http://slashdot.org/index.rss 5 author date 1h }}
```

- (BeauHD (2026/09/10 03:30 بواسطة [Anthropic Reveals Fourth Likely Crime Committed By Its AI](#) •
- BeauHD (2026/09/09 بواسطة [Google to Invest Record \\$15 Billion In AI Infrastructure In Finland](#) •
(23:00
- BeauHD بواسطة [Apple's New iPhone Camera Mode Promises to Prove Your Photo Isn't AI](#) •
((2026/09/09 22:00
- BeauHD بواسطة ['Anthropic Researcher Believes More Than 10% Chance AI 'Could Kill All Humans](#) •
((2026/09/09 21:00
- بواسطة [OpenAI's Rogue Agents Used At Least 10 More Sites For Unauthorized Communications](#) •
(BeauHD (2026/09/09 20:00

Control Macros

Some syntax influences how DokuWiki renders a page without creating any output it self. The following control macros are available

Description	Macro
If this macro is found on the page, no table of contents will be created	~~NOTOC~~

Description	Macro
DokuWiki caches all output by default. Sometimes this might not be wanted (eg. when the <php> syntax above is used), adding this macro will force DokuWiki to rerender a page on every call	~~NOCACHE~~

Syntax Plugins

DokuWiki's syntax can be extended by [Plugins](#). How the installed plugins are used is described on their appropriate description pages. The following syntax plugins are available in this particular :DokuWiki installation

- [Innovakom + CosmoCode بواسطة Diagrams plugin 2025-10-15](#) •
(Embed diagrams.net editor (formerly draw.io
- [Andreas Gohr and Luigi Micco بواسطة Dw2Pdf plugin 2023-11-25](#) •
DokuWiki to PDF converter
- [Gina Häußge, Michael Klier, Esther Brunner بواسطة Editor Plugin 2020-12-13](#) •
Displays a list of recently changed wiki pages by a given author
- [Andreas Gohr بواسطة Encrypted Passwords Plugin 2023-12-20](#) •
This plugin let you store 256 bit AES encrypted passwords in your DokuWiki pages. The
(password can be decrypted by clicking them (Javascript must be enabled
- [Michael Hamann, Gina Häussge, Christopher Smith, Michael بواسطة include plugin 2025-07-22](#) •
[Klier, Esther Brunner](#)
Functions to include another page in a wiki page
- [Andreas Gohr بواسطة Info Plugin 2020-06-04](#) •
Displays information about various DokuWiki internals
- [Matthias Schulte, Michael Hamann, Michael Klier, Gina بواسطة Pagelist Plugin 2023-08-27](#) •
[Haeussge](#)
Lists pages in a nice formatted way
- [Andreas Gohr, Michael Große, Anna Dabrowska بواسطة struct plugin 2025-09-24](#) •
Add and query additional structured page data
- [Michael Hamann, Gina Häussge, Christopher Smith, Michael Klier, بواسطة Tag Plugin 2023-10-17](#) •
[Esther Brunner](#)
tag wiki pages

(1)

This is a footnote

(2)

when the aspect ratio of the given width and height doesn't match that of the image, it will be cropped to the new ratio before resizing



From:
[/https://wiki.alshalbi.com](https://wiki.alshalbi.com) - أبو زيد الشلبي

Permanent link:
<https://wiki.alshalbi.com/doku.php?id=wiki:syntax>

Last update: **2026/07/14 20:15**